



Serie FRL 90

Standardverdrahtung / Electrical connection



Flanschdose männlich (Ansicht auf Steckerseite)
Connector male (View from face side)

SFP16 (16 Pin) DIN

MS 3102 A20-29P (17 Pin) MIL

Drahtfarbe Wire colour	Schalter Switches	Anschluss Function	Pin-Nr.	Pin-Nr.
Black	1	COM (1) NC (2)	1	A
White		NO (3)	2	B
Black	2	COM NC	3	C
Brown		NO	4	D
Black	3	COM NC	5	E
Green		NO	6	F
Black	4	COM NC	7	G
Yellow		NO	8	H
Black	5	COM NC	9	J
Grey		NO	10	K
Black	6	COM NC	11	L
Pink		NO	12	M
Black	7	COM NC	13	N
Blue		NO	14	P
Black	8	COM NC	15	R
Red		NO	16	S

Technische Änderungen vorbehalten / Subject to change without prior notice

Serie FRL 90

Anschlüsse mit Stecker / Connection with connector
Signalfarben nach / Cable designation at
Kabelquerschnitt für Schalter / Cable section for switches

COM-NO (2,8 x 0,5 mm)
DIN 47100
0.34 mm² / AWG 22

Zubehör / Accessories

Befestigungsbride / Hold down clamp
Programmierschlüssel / Program key

3 x BMF (M3x12 mm)
PSN

Option

Gegenstecker gerade (weiblich) / Female cable connector straight plug
Gegenstecker gerade (weiblich) / Female cable connector straight plug
Gegenstecker 90° (weiblich) / Female right angle connector 90°

SGS16.PG9 (16 Pin) DIN
MS 3106 A 20-29S (17 Pin) MIL
MS 3108 B 20-29S (17 Pin) MIL